

DATA SHEET



YACHT VARNISH

PRODUCT DATA

Our yacht varnish is a highly durable exterior varnish with excellent coverage, good weathering and UV resistant, non-yellowing, this varnish is only suitable for above the water line.

AREA OF USE: Exterior

SUBSTRATES: Wood

PACKING: 1 litre and 2.5 litres (min batch 100 litres)

PHYSICAL CONSTANTS:

Colour:	Clear
Finish:	Gloss
Volume solids:	42%
Theoretical spreading rate:	16 sq.metres per litre
Flash point:	38 °C
Specific gravity:	0.92
Dry to touch:	1-2 hours
Overcoating time:	16 hours

*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.

APPLICATION DETAILS:

Application method:	Brush, conventional and airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

SURFACE CONDITION: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

Please refer to the Material Safety Data Sheet for further information. For additional guidance please contact SML PAINTS.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.